

Sentinel 626

CARPET ADHESIVE REMOVER

- Odorless
- Nonflammable
- Biodegradable
- Removes Carpet and Latex Glue



SENTINEL® 626™ is a powerful, biodegradable formulation designed specifically for quickly removing latex, acrylic and pressure sensitive adhesives from concrete, terrazzo, ceramic and vinyl tile or wood substrates. **For best results use at room temperature and read instructions before using.**

SPECIFICATIONS

APPEARANCE.....	CLEAR	ODOR.....	NONE
APPROX. BOILING POINT.....	212° F.	SPECIFIC GRAVITY (TEMP).....(60° F)	>1
VAPOR DENSITY.....	HEAVIER THAN AIR	FLASHPOINT.....	NONE

DIRECTIONS

Removal of latex, acrylic and pressure sensitive adhesives:

Step One: Apply 626™ directly onto the adhesive. Use a broom, mop or squeegee to agitate and maintain even coverage while keeping the adhesive surface wet. Allow 626™ to soak and penetrate for 30-60 minutes.

Step Two: Scrape softened adhesive from the floor (razor scrapers or squeegees are generally preferred). Repeat steps one and two if necessary and dispose of the waste.

Step Three: Rinse the sub-floor thoroughly with clean water. Allow surface to dry.

Removal of sheet vinyl/linoleum backing: Once the wear layer is removed, mix 1 part HOT water to 4 parts 626™ (1 quart of HOT water to 1 gallon of 626™) and apply directly to the remaining backing. Maintain even coverage and a wet surface for 1-2 hours or until backing and adhesive can be easily removed together with floor scrapers. Rinse the surface with clean water, and allow to dry.

Removal of carpeting: Using a utility knife, cut the carpeting in 1-foot strips (making sure to cut through the carpeting to the sub-floor). Mix 1 part HOT water to 1 part 626™ (1 gallon HOT water to 1 gallon 626™) and pour directly onto carpet to be removed. Maintain even coverage and completely saturate carpeting with 626™ . Allow to soak 4 hours or overnight. Pick up carpet strips and follow latex removal procedures.

Coverage for the mastic remover will range from 25-75 square feet per gallon.

For additional information, contact Sentinel's Customer Service at 800-373-0633 or on the web at www.senpro.com

51 NE 77th Ave
Mpls, MN 55432



800-373-0633
Fax 763-571-1819